

| Stock Number   | Description   |
|--|---|
| <b>UNI-DIRECTIONAL FABRICS</b>   |   |
| UD-200-13-60   | <b>Unidirectional</b> Basalt fabric, 200 grams/sq. meter (5.9 oz./sq. yard), width 60 cm. (23.6"). Made with 13 micron roving. Roll length 50 meters or 100 meters.   |
| UD-200-13-10   | <b>Unidirectional</b> Basalt fabric, 200 grams/sq. meter (5.9 oz./sq. yard), width 10 cm. (3.9"). Made with 13 micron roving. Roll length 100 meters.   |
| UD-200-13-50-B<br><b>(NOT STD INVENTORY)</b>   | <b>Black Unidirectional</b> fabric, 200 grams/sq. meter (5.9 oz./sq. yard), width 50 cm. (19.7"). Made with <b>Black</b> 13 micron roving. Roll length 50 meters.   |
| UD-250-13-100  | <b>Unidirectional</b> Basalt fabric, 250 grams/sq. meter (7.33 oz./sq. yard), width 100 cm. (39.4"). Made with 13 micron roving. Roll length 50 meters.   |
| UD-280-13-60   | <b>Unidirectional</b> Basalt fabric, 280 grams/sq. meter (8.2 oz./sq. yard), width 60 cm. (23.6"). Made with 13 micron roving. Roll length 100 meters.  |
| UD-300-13-60   | <b>Unidirectional</b> Basalt fabric, 300 grams/sq. meter (8.8 oz./sq. yard), width 60 cm. (23.6"). Made with 13 micron roving. Roll length 100 meters.  |
| UD-400-13-60   | <b>Unidirectional</b> Basalt fabric, 400 grams/sq. meter (11.7 oz./sq. yard), width 60 cm. (23.6"). Made with 13 micron roving. Roll length 50 meters ..  |
| <b>LIMITED INVENTORY</b> <span style="float: right;"><b>MULTI-DIRECTIONAL FABRICS</b></span> |   |
| <del>BA 450 13 0.90 25.4</del>   | <del><b>Bi-Axial</b> Basalt Fabric, weight 450 grams/sq. meter (13.2 oz./sq. yard), width 25.4 cm. (10") Fiber orientation 0 degrees, 90 degree. Made with 13 micron roving. Roll length 54 meters.</del>                       |
| BA-450-13-0.90-127   | <b>Bi-Axial</b> Basalt Fabric, weight 450 grams/sq. meter (13.2 oz./sq. yard), width 127 cm. (50") Fiber orientation 0 degrees, 90 degree. Made with 13 micron roving. Roll length 25 meters.                                   |
| <del>BA 650 13 0.90 31.8</del>   | <del><b>Bi-Axial</b> Fabric, weight 650 grams/sq. meter (19 oz./sq. yard), width 31.8 cm. (12.5") Fiber orientation 0 degree, 90 degree. Made with 13 micron roving. Roll length 25 meters.</del>                               |
| BA-650-13-0.90-127   | <b>Bi-Axial</b> Basalt Fabric, weight 650 grams/sq. meter (19 oz./sq. yard), width 127 cm. (50") Fiber orientation 0 degrees, 90 degree. Made with 13 micron roving. Roll length 25 meters.                                     |
| <del>BA 650 13 +45. 45 127</del>   | <del><b>Bi-Axial</b> Basalt Fabric, weight 650 grams/sq. meter (19 oz./sq. yard), width 127 cm. (50") Fiber orientation +45 degrees, - 45 degree. Made with 13 micron roving. Roll length 25 meters.</del>                      |
| <del>TA 080 13 0.+45. 45 32</del>  | <del><b>Tri-Axial</b> Basalt Fabric, weight 980 grams/sq. meter (28.7 oz./sq. yard), width 32 cm. (12.6") Fiber orientation 0 degree, +45 degrees, - 45 degree. Made with 13 micron roving. Roll length 50 meters.</del>        |
| <del>QA 680 13 0.90,+45, 45 127</del>  | <del><b>Quad Axial</b> Basalt Fabric, weight 680 grams/sq. meter (19.9 oz./sq. yard), width 127 cm. (50") Fiber orientation 0 degree, 90 degree +45 degree -45 degree. Made with 13 micron roving. Roll length 50 meters.</del> |
| <b>PLAIN WEAVE FABRICS</b>   |   |
| PW-100-9-120<br><b>(NOT STD INVENTORY)</b>   | <b>Plain</b> weave Basalt 15x15 fabric, weight 100 grams/sq. meter (2.9 oz./sq. yard) width 120 cm.( 47.2 inches) Woven with 33 tex 9 micron yams, Roll length 50 meters.   |
| PW-108-9-56  | <b>Plain</b> weave Basalt 15x15 fabric, weight 108 grams/sq. meter (3.2 oz./sq. yard) width 56 cm.( 22 inches) Woven with 88 tex 7 mcron yams,. Roll length 100 meters.   |
| PW-160-11-127  | <b>Plain</b> weave Basalt fabric, weight 160 grams/sq. meter (4.7 oz./sq. yard) width 127 cm. (01 inches) Made with 11 micron fibers. Roll length 100 meters.   |
| PW-180-11-100  | <b>Plain</b> weave Basalt fabric, weight 180 grams/sq. meter (5.3 oz./sq. yard) width 100 cm. (39.4 inches) Woven with 100 tex 11 micron yams, S30 twist.. Roll length 25 meters.   |
| PW-200-7-100   | <b>Plain</b> weave Basalt fabric, weight 200 grams/sq. meter (5.9 oz./sq. yard) width 100 cm. (39.4 inches) Woven with 88 tex 7 micron yarn. Density 11x11 ends/cm. Roll length 100 meters.                                     |
| PW-200-11-100  | <b>Plain</b> weave Basalt fabric, weight 200 grams/sq. meter (5.9 oz./sq. yard) width 100 cm. (39.4 inches) Woven with 11 micron fibers. Roll length 100 meters.  |
| PW-200-13-100  | <b>Plain</b> weave Basalt fabric, weight 200 grams/sq. meter (5.9 oz./sq. yard) width 100 cm. (39.4 inches) Woven with 13 micron fibers. Roll length 100 meters.  |
| PW-350-13-100  | <b>Plain</b> weave Basalt fabric, weight 350 grams/sq. meter (10.26 oz./sq. yard) width 100 cm. (39.4 inches) Density 5 yams/cm. X 5 yams/cm. (12.7 x 12.7 yams/inch) Made with 13 micron fibers. Roll length 50 meters.        |
| PW-650-13-100  | <b>Plain</b> weave Basalt 5x3 fabric, weight 650 grams/sq. meter (19 oz./sq. yard) width 100 cm. (39.4 inches) Made with 13 micron fibers. Roll length 50 meters.   |

| <b>TWILL WEAVE FABRICS</b>                 |   |  |
|--|---|--|
| TW-200-13-100                              | <b>Twill</b> weave Basalt 8x7 fabric, weight 200 grams/sq. meter (5.9 oz./sq. yard) width 100 cm.( 39.4 inches) Made with 13 micron fibers. Loose Weave. Roll length 50 meters.   |  |
| TW-300-13-100                              | <b>Twill</b> weave Basalt 5x5 fabric, weight 300 grams/sq. meter (8.8 oz./sq. yard) width 100 cm.( 39.4 inches) Made with 13 micron fibers. Loose weave. Roll length 50 meters..  |  |
| TW-600-13-100                              | <b>Twill</b> weave Basalt 5x5 fabric, weight 600 grams/sq. meter (17.6 oz./sq. yard) width 100 cm.( 39.4 inches) Made with 13 micron fibers. Tightly woven. Roll length 50 meters.  |  |
| TW-900-13-100                              | <b>Twill</b> weave Basalt 6x6 fabric, weight 900 grams/sq. meter (26.4 oz./sq. yard) width 100 cm.( 39.4 inches) Made with 13 micron fibers. Tightly woven. Roll length 50 meters.  |  |
| <b>SATIN WEAVE FABRICS</b>                 |   |  |
| SW-220-9-100                               | <b>Satin</b> weave Basalt fabric, weight 220 grams/sq. meter (6.45 oz./sq. yard) width 100 cm.( 39.4 inches) Made with 9 micron fibers. Roll length 50 meters.  |  |
| SW-300-9-127                               | <b>Satin</b> weave fabric, weight 300 grams/sq. meter (8.8 oz./sq. yard) width 127 cm.( 50 inches) Made with 9 micron fibers. Roll length 50 meters.  |  |
| SW-320-9-127                               | <b>Satin</b> weave fabric, weight 320 grams/sq. meter (9.4 oz./sq. yard) width 127 cm.( 50 inches) Made with 9 micron fibers. Roll length 25 meters.  |  |
| SW-420-9-100                               | <b>Satin</b> weave basalt fabric, weight 420 grams/sq. meter (12.3 oz./sq. yard). Width 100 cm (39.36 inches). Made with 9 micron roving. Roll length 50 meters   |  |
| <b>COATED FABRICS</b>                      |   |  |
| CAL-PW-220-14-138                          | <b>Aluminum Coated one side</b> Basalt Plain Weave Fabric. 7.2x7.2 ends/cm., weight 220 grams/sq. meter (6.45 oz./sq. yard) width 138 cm. (54.3 inches) Made with 19 micron fibers. Roll length 25 meters. Weight does not include aluminum film. |  |
| CAL-SW-300-9-127<br>Limited Availability   | <b>Aluminum Coated one side</b> Basalt Plain Weave Fabric. Weight 320 grams/sq. meter (8.8 oz./sq. yard) width 127 cm. (50 inches) Made with 9 micron fibers. Roll length 25 meters. Weight does not include aluminum film.                       |  |
| CAL-SW-320-9-127                           | <b>Aluminum Coated one side</b> Basalt Plain Weave Fabric. Weight 300 grams/sq. meter (9.4 oz./sq. yard) width 127 cm. (50 inches) Made with 9 micron fibers. Roll length 25 meters. Weight does not include aluminum film.                       |  |
| CAL-PW-650-100                             | <b>Aluminum Coated one side</b> Basalt Plain Weave Fabric. Weight 650 grams/sq. meter (19 oz./sq. yard) width 100 cm. (39.4 inches) Made with 13 micron fibers. Roll length 25 meters. Weight does not include aluminum film.                     |  |
| CS-TW-680-13-125                           | <b>Basalt twill weave fabric, coated on side with silicone rubber.</b> Weight 680 grams/sq. meter (19.9 oz./sq. yard) Width 125 cm. (49.25") Woven with s13 micron filaments. Roll length 50 meters.  |  |
| CAL-TW-900-100                             | <b>Aluminum Coated one side</b> Basalt Twill Weave Fabric. Weight 900 grams/sq. meter (26.4 oz./sq. yard) width 100cm. (39.4 inches) Made with 13 micron fibers. Roll length 25 meters. Weight does not include aluminum film.                    |  |
| CAL2-TW-900-100                            | <b>Aluminum Coated both sides</b> Basalt Twill Weave Fabric. Weight 900 grams/sq. meter (26.4 oz./sq. yard) width 100cm. (39.4 inches) Made with 13 micron fibers. Roll length 25 meters. Weight does not include aluminum film.                  |  |
| <b>SURFACE VEILS (WET-LAID NON-WOVENS)</b> |   |  |
| SV-30-100                                  | <b>Surface veil</b> (wet laid non-woven) weight 30 grams/sq. meter (0.88 oz./sq. yard) width 100 cm. (39.37") Roll length 100 meters. <b>Sold in full rolls only</b>  |  |
| SV-40-100                                  | <b>Surface veil</b> (wet laid non-woven) weight 40 grams/sq. meter (1.17 oz./sq. yard) width 100 cm. (39.37") Roll length 100 meters. <b>Sold in full rolls only</b>  |  |
| <b>CHOPPED STRAND MAT</b>                  |   |  |
| BCSM-200-100                               | <b>Basalt Chopped Strand Mat</b> , weight 200 grams/sq. meter (5.9 oz./sq. yard). Width 100 cm. (39.4 inches) Roll length 50 meters. <b>Sold in full rolls only</b>   |  |
| BCSM-350-100                               | <b>Basalt Chopped Strand Mat</b> , weight 350 grams/sq. meter (10.25 oz./sq. yard). Width 100 cm. (39.4 inches) Roll length 100 meters. <b>Sold in full rolls only</b>  |  |
| <b>LIMITED INVENTORY</b>                   | <b>BASALT WOVEN TAPE</b>  |  |
| BWT-25-1                                   | <b>Basalt Woven Tape</b> Width 25mm. Packed on 100 meter rolls.   |  |
| BWT-50-3                                   | <b>Basalt Woven Tape</b> Width 50mm. Packed on 50 meter rolls. <b>Small polyester edge thread.</b>  |  |

|   |  |
|---|--|
| BWT-75-1  | <b>Basalt Woven Tape</b> Width 75mm. Packed on 100 meter rolls.  |
| BWT-100-1   | <b>Basalt Woven Tape</b> Width 100mm. Packed on 100 meter rolls.   |
| BWT-135-1   | <b>Basalt Woven Tape</b> Width 135mm. Packed on 100 meter rolls.   |
| BWT-25-2  | <b>Basalt Woven Tape</b> Width 25mm. Heavy weight- 2mm thick. Packed on 25 meter rolls   |
| BWTT-50-1   | <b>Basalt Twill Woven Tape</b> Width 50mm. Packed on 25 meter rolls  |
| CAL-BWT-50-1  | <b>Basalt Plain Weave Tape, aluminum coated one side</b> Width 50mm. Packed on 7.8 meter rolls (25 feet).  |
| <b>BASALT BI-AXIAL BRAIDED SLEEVING</b>   |  |
| BBS-2   | <b>Basalt Biaxial Braided Sleeving Diameter 2cm.</b> Braided with Basalt Twisted Yam. Roll length 50 meters.   |
| BBS-3   | <b>Basalt Biaxial Braided Sleeving Diameter 3cm.</b> Braided with Basalt Twisted Yam. Roll length 50 meters  |
| BBS-4   | <b>Basalt Biaxial Braided Sleeving Diameter 4cm.</b> Braided with Basalt Twisted Yam. Roll length 50 meters.   |
| BBS-5   | <b>Basalt Biaxial Braided Sleeving Diameter 5 cm.</b> Braided with Basalt Twisted Yam. Roll length 50 meters.  |
| BBS-7   | <b>Basalt Biaxial Braided Sleeving Diameter 7 cm.</b> Braided with Basalt Twisted Yam. Roll length 25 meters.  |
| BBS-10  | <b>Basalt Biaxial Braided Sleeving Diameter 10cm.</b> Braided with Basalt Twisted Yam. Roll length 50 meters.  |
| BBS-12  | <b>Basalt Biaxial Braided Sleeving Diameter 12 cm.</b> Braided with Basalt Twisted Yam. Roll length 25 ft. (7.62 meters)   |
| BBS-15  | <b>Basalt Biaxial Braided Sleeving Diameter 15 cm.</b> Braided with Basalt Twisted Yam. Roll length 25 ft. (7.62 meters)   |
| BBS-20  | <b>Basalt Biaxial Braided Sleeving Diameter 20 cm.</b> Braided with Basalt Twisted Yam. Roll length 25 ft. (7.62 meters)   |
| <b>BASALT MACROFIBERS</b>   |  |
| BMFT-25   | <b>Basalt Macrofiber, length 25mm. Twisted type.</b> Designed for concrete reinforcement. Packed in 10 kg. bags.   |
| BMFT-43   | <b>Basalt Macrofiber, length 43mm. Twisted type.</b> Designed for concrete reinforcement. Packed in 10 kg. bags.   |
| BMFW-25   | <b>Basalt Macrofiber, length 25mm. Waved type.</b> Designed for concrete reinforcement. Packed in 10 kg. bags.   |
| BMFW-43   | <b>Basalt Macrofiber, length 43mm. Waved type.</b> Designed for concrete reinforcement. Packed in 10 kg. bags.   |
| <b>CHOPPED FIBER</b>  |  |
| <b>October 2023: Polypropylene BCF-3-13-322 (previously BCF-3-13-5). Polyamide BCF-3-13-316A (previously BCF-3-13-6). Polycarbonate BCF-3-13-318.</b> |  |
| BCF-3-13-1  | <b>Basalt chopped fiber</b> length 3mm diameter 13 microns. Sizing for epoxy/polyester/pva resins. Packed in 20 kg. bags (44lb)                                  |
| BCF-3-13-4  | <b>Basalt chopped fiber</b> length 3mm diameter 13 microns. Sizing for phenolic resins. Also good for Portland Cement applications. Packed in 20 kg. bags (44lb) |
| <del>BCF-3-13-5</del><br>BCF-3-13-322   | <b>Basalt chopped fiber</b> length 3mm diameter 13 microns. Sizing for polypropylene resins.. Packed in 20 kg. bags (44lb)                                       |
| <del>BCF-3-13-6</del><br>BCF-3-13-316A  | <b>Basalt chopped fiber</b> length 3mm diameter 13 microns. Sizing for polyamide resins. Packed in 20 kg. bags (44lb)  |
| BCF-6-13-1  | <b>Basalt chopped fiber</b> length 6mm diameter 13 microns. Sizing for epoxy/polyester/pva resins. Packed in 20 kg. bags (44lb)                                  |
| BCF-6-13-4  | <b>Basalt chopped fiber</b> length 6mm diameter 13 microns. Sizing for phenolic resins. Also good for Portland Cement applications. Packed in 20 kg. bags (44lb) |
| <del>BCF-6-13-5</del><br>BCF-6-13-322   | <b>Basalt chopped fiber</b> length 6mm diameter 13 microns. Sizing for polypropylene resins. Packed in 20 kg. bags (44lb)  |
| <del>BCF-6-13-6</del><br>BCF-6-13-316A  | <b>Basalt chopped fiber</b> length 6mm diameter 13 microns. Sizing for polyamide resins. Packed in 20 kg. bags (44lb)  |
| BCF-9-13-3  | <b>Basalt chopped fiber</b> length 9mm diameter 13 microns. Has special sizing for asphalt applications. Packed in <b>35 kg. bags - 77.16 lbs.</b>               |
| BCF-12-16-1   | <b>Basalt chopped fiber</b> length 12mm diameter 16 microns. Sizing for epoxy/polyester/pva resins. Packed in 20 kg. bags (44lb)                                 |
| BCF-12-17-2   | <b>Basalt chopped fiber</b> length 12mm diameter 16 microns. Sizing applied for Portland cement applications. Packed in 20 kg. bags (44lb)                       |
| BCF-18-17-2   | <b>Basalt chopped fiber</b> length 18mm diameter 20 microns. Sizing applied for Portland cement applications. Packed in <b>25 kg. bags - 55 lbs</b>              |

|                       |  |
|-----------------------|--|
| BCF-25-17-2           | <b>Basalt chopped fiber</b> length 25mm diameter 17 microns. Sizing applied for Portland cement applications. Packed in 20 kg. bags (44lb)   |
| BCF-24-13-1           | <b>Basalt chopped fiber</b> length 24mm diameter 13 microns. Sizing for epoxy/polyester/pva resins. Packed in 20 kg. bags (44lb)   |
| BCF-36-13-1           | <b>Basalt chopped fiber</b> length 36mm diameter 13 microns. Sizing for epoxy/polyester/pva resins. . Packed in 20 kg. bags (44lb)   |
| BCF-36-17-2           | <b>Basalt chopped fiber</b> length 36mm diameter 17 microns. Sizing applied for Portland cement applications. Packed in 20 kg. bags (44lb)   |
| BCF-50-13-1           | <b>Basalt chopped fiber</b> length 50mm diameter 13 microns. Sizing for epoxy/polyester/pva resins. Packed in 20 kg. bags (44lb)   |
| BCF-50-17-2           | <b>Basalt chopped fiber</b> length 50mm diameter 17 microns. Sizing applied for Portland cement applications. Packed in <b>20 kg. bags (44lb)</b>  |
| BCF-90-13-1           | <b>Basalt chopped fiber</b> length 90mm diameter 13 microns. Sizing for epoxy/polyester/pva resins. Packed in 20 kg. bags (44lb)   |
| <b>BASALT YARNS</b>   |  |
| BCR-11-7 S80          | <b>Basalt twisted yarn.</b> Tex 11 (yield 45,174) , filament diameter 7 microns. Twist S80. Consists of 100 7 micron filaments. Packaged on 0.5 kg. milk bottle bobbin. Sizing for epoxy/polyester/pva resins.                                   |
| BCR-16.5-6 S80        | <b>Basalt twisted yarn.</b> Tex 16.5 (30,090 yield) , filament diameter 6 microns. Twist S80. Consists of 200 6 micron filaments. Packaged on 0.5 kg. milk bottle bobbin. Sizing for epoxy/polyester/pva resins.                                 |
| BCR-22-7 S80          | <b>Basalt twisted yarn.</b> Tex 22 (yield 22,587) , filament diameter 7 microns. Twist S80. Consists of 200 7 micron filaments. Packaged on 0.5 kg. milk bottle bobbin. Sizing for epoxy/polyester/pva resins.                                   |
| BCR-33-9 S80          | <b>Basalt twisted yarn.</b> Tex 33 (yield 15,045 yield) , filament diameter 9 microns. Twist S80. Consists of 200 9 micron filaments. Packaged on 0.5 kg. milk bottle bobbin. Sizing for epoxy/polyester/pva resins.                             |
| BCR-66-9 S20          | <b>Basalt twisted yarn.</b> 9 micron filament diameter, 66 tex (7523 yield). Twist 20 turns/meter. Packed on 0.5 kg. outside pull "milk bobble" bobbins. Sizing for epoxy/polyester/pva resins.  |
| BCR-66-9 S300         | <b>Basalt twisted yarn.</b> 9 micron filament diameter, 66 tex (7523 yield). Twis 300 turns/meter. Packed on 1 kg. outside pull "milk bobble" bobbins. <b>Can be used for sewing.</b> Sizing for epoxy/polyester/pva resins. <b>Out of stock</b> |
| BCR-76-9 S270         | <b>Basalt twisted yarn.</b> 9 micron filament diameter, 76 tex (6530 yield). Twis 270 turns/meter. Packed on 1 kg. outside pull "milk bobble" bobbins. <b>Can be used for sewing.</b> Sizing for epoxy/polyester/pva resins.                     |
| <b>BASALT ROVINGS</b> |  |
| BCR-100-11            | <b>Basalt continuous roving</b> 11 micron diameter, 100 tex (4,965 yield) Packed on 0.5 kg. outside pull bobbins   |
| BCR-136-9             | <b>Basalt continuous roving</b> 9 micron diameter, 136 tex (3650 yield) Packed on 1 kg. outside pull bobbins. Sizing for epoxy/polyester/pva resins.   |
| BDR-198-13            | <b>Basalt Direct Roving</b> 198 tex (2507 yield). 13 micron diameter, 600 filament direct roving. Packed on 6 kg. Inside pull bobbins. Sizing for epoxy/polyester/pva resins.  |
| BDR-264-13            | <b>Basalt Direct Roving</b> 13 micron diameter, 264 tex 1881 yield). 800 filament direct roving. Packed on 6 kg. Inside pull bobbins. Sizing for polyester resins.   |
| BCR-264-13            | <b>Basalt continuous roving</b> 13 micron diameter, , tex 264 (1881 yield) packed on 2 kg outside pull bobbins. Sizing for epoxy/polyester/pva resins.   |
| BCR-800-13            | <b>Basalt continuous roving</b> 13 micron diameter, 800 tex (621 yield) Packed on 2 kg outside pull bobbins, and 10 kg. inside pull bobbins Sizing for epoxy/polyester/pva resins.   |
| BCR-1200-13-1         | <b>Basalt continuous roving</b> 13 micron diameter, 1200 tex (414 yield) Packed on 1 kg outside pull bobbins, 2 kg outside pull bobbins, and 10 kg. inside pull bobbins. Sizing for epoxy/polyester/pva resins.                                  |
| BCR-1200-13-5         | <b>Basalt continuous roving</b> 13 micron diameter, 1200 tex (414 yield) Sizing for thermoplastic resins. Packed on 2 kg outside pull bobbins.   |
| BCR-2400-16           | <b>Basalt continuous roving</b> 16 micron diameter, 2400 tex (207 yield) Packed on 2 kg outside pull bobbins, and 10 kg. inside pull bobbins. Sizing for epoxy/polyester/pva resins.   |
| BCR-4800-16           | <b>Basalt continuous roving</b> 16 micron diameter, 4800 tex (103 yield) Packed on 2 kg outside pull bobbins, and 10 kg. inside pull bobbins. Sizing for epoxy/polyester/pva resins.   |
| BHTR-4800-17          | <b>Basalt continuous roving</b> 17 micron diameter, 4800 tex (103 yield) Has higher temperature tolerance. Packed on 2 kg outside pull bobbins. Sizing for texturizing.  |

|  |   |
|--|---|
|  | <b>BASALT SEWING THREAD</b>   |
| BST-146-6                                | <b>Basalt Sewing Thread.</b> Total tex 146. Made with 3 plies of 6 micron roving, each ply madeup of three plies of 16.5 tex 6 micron 200 filament roving. Total 1800 filements. Packed on 0.5 kg milk-bottle bobbins.                |
| BST-146-6-TC                             | <b>Basalt Sewing Thread. Teflon Coated.</b> Total tex 146. Made with 3 plies of 6 micron roving, each ply madeup of three plies of 16.5 tex 6 micron 200 filament roving. Total 1800 filements. Packed on 0.5 kg milk-bottle bobbins. |
|  | <b>BASALT TEXTURIZED YARN</b>   |
| BTY-800-13                               | <b>Basalt Texurized Yarn.</b> Tex 800. Filament diameter 13 microns. Packed on 4 kg. outside pull bobbins.  |
| BTY-1400-13                              | <b>Basalt Texurized Yarn.</b> Tex 1400. Filament diameter 13 microns. Packed on 4 kg. outside pull bobbins.   |
|  | <b>BASALT GUN ROVING</b>  |
| BGR-2400-15                              | <b>Basalt gun roving</b> 15 micron diameter, 2400 tex (207 yield) Packed on 16.5 kg. inside pull bobbins. For concrete applications.  |
|  | <b>BASALT 3-PLY ROPE</b>  |
| BCR-3P-19,200-16                         | <b>Basalt 3-ply rope.</b> Made from 3 plies of 6400 tex 16 micron roving, total tex 19,200. Packed on 7 kg spools. <b>Designed for reinforcing concrete.</b>  |
|  | <b>BASALT REBAR -- Coils</b>  |
| BRB-4                                    | <b>Basalt rebar, diameter 4mm.</b>  |
| BRB-6                                    | <b>Basalt rebar, diameter 6mm.</b>  |
| BRB-8                                    | <b>Basalt rebar, diameter 8mm.</b>  |
| BRB-10                                   | <b>Basalt rebar, diameter 10mm.</b>   |
|  | Note: Rebar greater than 10mm diameter cannot be coiled.  |
|  | <b>BASALT REBAR -- Sticks</b>   |
| BRB-12                                   | <b>Basalt rebar, diameter 12mm.</b>   |
| BRB-14                                   | <b>Basalt rebar, diameter 14mm</b>  |
| BRB-16                                   | <b>Basalt rebar, diameter 16mm</b>  |
| BRB-18                                   | <b>Basalt rebar, diameter 18mm</b>  |
| BRB-20                                   | <b>Basalt rebar, diameter 20mm</b>  |
| BRB-22                                   | <b>Basalt rebar, diameter 22mm</b>  |
| BRB-25                                   | <b>Basalt rebar, diameter 25mm</b>  |
| <b>LIMITED INVENTORY</b>                 | <b>BASALT REBAR Elbows -- Bent 90 Degrees</b>   |
| BRB-8-90-1M                              | <b>Basalt rebar, diameter 8mm. Bent 90 degrees.</b> Leg lenghs 1 meter x 1 meter. Total length 2 meters.  |
| BRB-10-90-1M                             | <b>Basalt rebar, diameter 10mm. Bent 90 degrees.</b> Leg lenghs 1 meter x 1 meter. Total length 2 meters.   |
| BRB-10-90-24"                            | <b>Basalt rebar, diameter 10mm. Bent 90 degrees.</b> Leg lengths 2 feet x 2 feet. Total length 4 feet.  |
| BRB-12-90-1M                             | <b>Basalt rebar, diameter 12mm. Bent 90 degrees.</b> Leg lenghs 1 meter x 1 meter. Total length 2 meters.   |
|  | <b>BASALT MESHES</b>  |
| Mesh-2-100-U                             | <b>Basalt mesh.</b> Window size 2mm x 2mm. No resin coating. Width 100 cm.cm (39.4 inches)  |
| Mesh-3-115-U                             | <b>Basalt mesh.</b> Window size 3mm x 3mm. No resin coating. Width 115cm (45.24 inches)   |
| Mesh-5-100                               | <b>Basalt mesh.</b> Window size 5mm x 5mm. Resin Coated. Width 100 cm (39.4 inches) Roll length 100 meters. Roll Total Area 100 sq. meters  |
| Mesh-5-100-U                             | <b>Basalt mesh.</b> Window size 5mm x 5mm. No resin coating. Width 100 cm (39.4 inches) Roll length 50 meters. Roll Total Area 50 sq. meters  |
| Mesh-6x8-600-13-88.4 (NOT STD INVENTORY) | <b>Basalt Mesh</b> Window size 6mm x 8mm. Weight 600 grams/sq. meter (17.6 oz./xq. Yard). No resin coating. Width 86.4 cm. (35")  |

|  |  |
|--|--|
| Mesh-6x8-600-13-110.5<br>(NOT STD INVENTORY) | <b>Basalt Mesh</b> Window size 6mm x 8mm. Weight 600 grams/sq. meter (17.6 oz./sq. Yard). No resin coating. Width 110.5 cm.( 44")  |
| Mesh-10-100                                  | <b>Basalt mesh.</b> Window size 10mm x 10mm. Resin coated. Width 100 cm (39.4 inches) Roll length 50 meters. Roll Total Area 50 sq. meters   |
| Mesh-10-100-U                                | <b>Basalt mesh.</b> Window size 10mm x 10mm. No resin coating. Width 100 cm (39.4 inches) Roll length 50 meters. Roll Total Area 50 sq. meters   |
| Mesh-25-100                                  | <b>Basalt mesh.</b> Window size 25mm x 25mm. Resin Coated. Width 100 cm (39.4 inches) Roll length 50 meters. Roll Total Area 50 sq. meters   |
| Mesh-50-100                                  | <b>Basalt mesh.</b> Window size 50mm x 50mm. Resin Coated. Width 100 cm (39.4 inches) Roll length 50 meters. Roll Total Area 50 sq. meters   |
| <b>BASALT NEEDLE FELT MAT</b>                |  |
| BNF-4-100                                    | <b>Basalt needle felt mat.</b> 4mm thick, 1.05 meter width (39.45") Roll length 50 meters. Roll area 50 sq. meters   |
| BNF-6-105-115                                | <b>Basalt needle felt mat.</b> 6mm thick, 1.05 meter width (41.5") Weight 682 grams/sq. meter (20 oz. /sq. yard) Density 115 kg./cu. meter (7 lbs./cu. foot). Roll length 25 meters. Rol area 26.25 sq. meters |
| BNF-8-100-115                                | <b>Basalt needle felt mat.</b> Thickness 8mm Width 100 cm. (39.4") Weight 890 grams/sq. meter (26 oz. /sq. yard) Density 115 kg./cu. meter (7 lbs./cu. foot) Roll length 20 meters                             |
| BNF-12-100-120                               | <b>Basalt needle felt mat.</b> Thickness 12mm Width 100 cm. (39.4") Weight 1425 grams/sq. meter (42 oz. /sq. yard) Density 120 kg./cu. meter (7.5 lbs./cu. foot) Roll length 16.5 meters or 20 meters          |
| BNF-25-100-135                               | <b>Basalt needle felt mat.</b> Thickness 25mm Width 100 cm. (39.4") Weight 3385 grams/sq. meter (99 oz. /sq. yard) Density 135 kg./cu. meter (9 lbs./cu. foot) Roll length 10 meters.                          |